# 1 fiber Single-Tube singlemode cable OptiTap to SC/APC Jumper

Assemblies



for more products please visit us on polyknitfabric.com

Tyson

Place of Origin:	Guangdong, China
<ul> <li>Brand Name:</li> </ul>	DYS/OEM
<ul> <li>Model Number:</li> </ul>	SC/APC
Minimum Order Quantity:	2 pieces
Price:	\$5.50 - \$15.00/pieces
Packaging Details:	1pc/PE bag according to customer's request.
<ul> <li>Supply Ability:</li> </ul>	20000 Piece/Pieces per Quarter



# **Product Specification**

Basic Information

• Туре:	FTTx Solutions
• Use:	FTTH, FTTH
Connector B Type:	OptiTap
Connector A Type:	SC/APC
<ul> <li>Product Type:</li> </ul>	FTTH Drop Cable Assemb
Application:	FTTA BBU RRU
• No. Of Fiber:	1.
Cable Diameter:	3.0mm,4.8mm Or 7.0mm
• Fiber Type:	Singlemode
• Fiber Brand:	Corning, YOFC, OFS
Length:	Customized

Customized Shenzhen



### More Images

• Port:



## Product Description

### Product Description

#### Hoptic assemblies matching with Corning Optitap

DYS's H optic assemblies provide a robust and sealed connection solution for fiber to the home (FTTH) connectivity. The H optic connector end Incorporates an SC/APC type connection within a slim, sealed, threaded polymer housing allowing easy connections of the multiport terminal or in-line extension receptacle. The SC/APC connector mates to a standard adapter, providing a common interface for FTTH applications. Available with flat drop or traditional round style OSP cables, the H optic connector provides an ideal solution for direct burial, conduit, or aerial installations.

Benefits

**Our Product Introduction** 

Allows flexibility to use factory terminated assemblies Provides superior weather resistance for FTTH and other outdoor applications Ensures functionality in harsh weather environments Can be used with industry standard cable designs Easily installs without special tooling Threaded style coupling Provides bend protection for installation and long term use Features

Single fiber, SC-based connector Bird proof and rodent resistant IP68 water and dust protection. Low profile in-line receptacle available. No Installation tools required 100 minimum mating cycles In-line connection available Operating temperature: -40° to 85°C Cable Diameter Range: 2.0mm, 3.0mm, 4.8mm to 7mm 33 lb. axial cable retention (150N) Applications

FTTH Outdoor Areas Harsh Environment









**Company Profile** 



Shenzhen DYS Fiber Optic Technology is a leading company in developing and manufacturing advanced fiber optic products mainly make fiber optic indoor and outdoor cable, CPRI waterproof jumper, MPO/MTP jumper , standard fiber optic jumper and PLC Splitter. DVS win the honorary title of National High-tech enterprise by Shenzhen government in 2014. With years of experiences in the fiber optic industry, our factory is fully equipped over 5000 square meters and more than 30 non dust production lines. About 250 well-trained staff and engineers are contributing to our proud products. We have 5 production lines for fiber optic cable, 2 high standard MPO/MTP jumper assembly lines, 15 production lines for standard jumper and 8 PLC Splitter production lines. The most advanced imported polishing equipment and testing instruments enable our products aver guere quality, such as Senko polishing machine, interferometer, automatic cleaning machine and OTDR JGR and so on. All of our optical products are RoHS compliant and DYS also obtained ISO9001, ISO14001 certification. Our high quality products and outstanding service win the customer from all the world, DYS fiber optic is looking forward to cooperate with you.



Tyson	Beijing Silk Road Enterprise Management Services Co.,LTD	
0	13299345678 🕑 13299345678@163.com 😢 polyknitfabric.com	
	19 Xinjian Gongmen Road, Haldian District, Beijing, China	