Our Product Introduction

₫

more products please visit us on polyknitfabric.com

# Compatible with Corning Optitap connector Waterproof SC/APC Fiber Optic patch cable

### **Basic Information**

• Place of Origin: Guangdong, China

. Brand Name: DYS Certification: RoHS, ce

 Model Number: Hoptic Connector patch cord • Price: \$6.00 - \$18.00/pieces

Individual box or according to customer's Packaging Details:

• Supply Ability: 20000 Piece/Pieces per Day



## **Product Specification**

Fiber Optic Cable . Type:

FTTX • Warranty Time: 5 Network: 4g, 3G

SC/APC Patch Cable Compatible With Product Name: Corning Optitap

OptiTap Connector SC/APC Connnector

• Fiber: SM G657A

3.0mm/4.6mm/ 4\*7mm Cable Size: 10M, 20M, 50M Or Customized Length:

Fiber Count: 1 Core Waterproof Grade: IP68 FTTH Application: • Certifaction: ISO9001, ROHS



### More Images


Connector A:

. Connector B:









### Product Description

### Product Description

### Compatible with Corning Optitap connector Waterproof SC/APC Fiber Optic patch cable

DYS's H opticassemblies provide a robust and sealed connection solution for fiber to the home (FTTH) connectivity. The H optic connector end To 3r Optication in the price of the connection within a slim, sealed, threaded polymer housing allowing easy connection to either a multiport terminal or in-line extension receptacle. The SC/APC connector mates to a standard adapter, providing a common interface for FTTH applications. Available with flat drop or traditional round style OSP cables, the H optic connector provides an ideal solution for direct burial, conduit, or aerial installations.

### Benefits


Allows flexibility to use factory terminated assemblies Provides superior weather resistance for FTTH and other outdoor applications Ensures functionality in harsh weather environments. Can be used with industry standard cable designs. Easily installs without special tooling. Threaded style coupling Provides bend protection for installation and long term use

### Features


Single fiber, SC-based connector Bird proof and rodent resistant IP68 water and dust protection. Low profile in-line receptacle available. No installation tools required 100 minimum mating cycles In-line connection available Operating temperature: -40° to 85°C Cable Diameter Range: 2.0mm, 3.0mm, 4.8mm to 7mm 33 lb. axial cable retention (150N)

Applications FTTH Outdoor Areas Harsh Environment

# Our Product Introduction








Working temperature

-40 to +85











# Outdoor Fiber Optic Cable Assembly



# Main Products



















Product inquiry



# Our Company

















# **PACKING & DELIVERY**







Wholesale orders

# **FAQ**

- How many staff's we have?
  Answer: About 250 well-trained staff and engineers

- What certificate we have? nawer. ISO 9001: 2015, RoSH, CE, High and New Tech Enterprise Certificate



Uson Beijing Silk Road Enterprise Management Services Co.,LTD





