Our Product Introduction

₫

more products please visit us on polyknitfabric.com

Optitap Connector Compatible Corning, SC Hardened Connector OptiTap Conector FTTA Patch Cord

Basic Information

• Place of Origin: Guangdong, China

• Brand Name: DYS

Model Number: IPSC-APC H Optic patch cord

• Price: \$8.50 - \$15.00/pieces

Packaging Details: Individual bag or according to customer's

request

• Supply Ability: 200000 Piece/Pieces per Week



Product Specification

Type: FTTx SolutionsUse: Fttx, FTTHNo. Of Fiber: 1.

Waterproof: IP67 IP68

• Fiber Type: G657A, G652D, Om1, Om2, Om3

• Diameter Size: 3.0mm,4.8mm, 7.0mm

Inserion Loss: <0.2db
Factory: Yes
Return Loss: >55db
3D Test: Available
Feature: Easy To Install
Port: Shenzhen



More Images









Product Description

Product Description

Optitap Connector Compatible Corning, SC Hardened Connector OptiTap Conector FTTA Patch Cord

DYS's H opticassemblies provide a robust and sealed connection solution for fiber to the home (FTTH) connectivity. The H optic connector end incorporates an SC/APC type connection within a slim, sealed, threaded polymer housing allowing easy connection to either a multiport terminal or in-line extension receptacle. The SC/APC connector mates to a standard adapter, providing a common interface for FTTH applications. Available with flat drop or traditional round style OSP cables, the H optic connector provides an ideal solution for direct burial, conduit, or aerial installations.

Benefits

Allows flexibility to use factory terminated assemblies Provides superior weather resistance for FTTH and other outdoor applications Ensures functionality in harsh weather environments Can be used with industry standard cable designs Easily installs without special tooling Threaded style coupling Provides bend protection for installation and long term use

Features

Single fiber, SC-based connector Bird proof and rodent resistant IP68 water and dust protection Low profile in-line receptacle available No installation tools required 100 minimum mating cycles In-line connection available Operating temperature: -40° to 85°C Cable Diameter Range: 2.0mm, 3.0mm, 4.8mm to 7mm 33 lb. axial cable retention (150N)

Applications

FTTH Outdoor Areas Harsh Environment









Main Products









Fiber Optic Cable

MPO/MTP









Product inquiry



Our Company

















PACKING & DELIVERY







Wholesale orders

FAQ

- How many staff's we have?
 Answer: About 250 well-trained staff and engineers

- What certificate we have? nawer. ISO 9001: 2015, RoSH, CE, High and New Tech Enterprise Certificate



Uson Beijing Silk Road Enterprise Management Services Co.,LTD





