Our Product Introduction

₫

more products please visit us on polyknitfabric.com

Field Assembly Reinforced Optical Connector OptiTap Adapter for SC Fast Connector

Basic Information

• Place of Origin: Guangdong, China

. Brand Name: DYS Certification: RoHS, ce

OptiTap Adapter For SC APC Fast Model Number:

\$1.00 - \$6.50/pieces

• Packaging Details: Individual bag or according to customer's

request

200000 Piece/Pieces per Quarter Supply Ability:



Product Specification

• Type: Fiber Adapter & Connectors

FTTA

 Model Name: Ttap For OptiTap Adapter

• Feature: Compatiable With Optitap (Corning) , $\mbox{\bf H}$

Connector (Amphenol)

Cable Type: Flat Drop Cable 3.0mm,5.0mm, Flat

2.0*3.0mm

IP68 Waterproof: No. Of Fiber: 1

Singlemode Fiber Type: Application: FTTX System <0.2db • Inserion Loss: >55db Material: PEI • Port: Shenzhen



More Images









Product Description

Product Description

Field Assembly Reinforced Optical Connector OptiTap Adapter for SC Fast Connector

- Compact size,easy to operate,durable.
 Easy connection to hardended adapters on terminals or closures.

- 2. Lasy commediation to include adapter or inferminate or includes.

 3. Reduce welding, connect directly to achieve interconnection.

 4. Spiral clamping mechanism ensures long-term reliable connection.

 5. Guide mechanism, can be blinded with one hand, simple and quick, connect and install.

 6. Accepts 2.0x3.0mm, 3.0mm, 5.0mm Cable Diameters Factory or field installation, Allows flexibility to use factory terminated and tested assemblies or retrofit to pre-terminated or field installed assemblies.

- Fiber optic communications in harsh outdoor environments.
 Outdoor communications equipment connection.
 Waterproof fiber equipment SC port.
 Remote wireless base station.
 FTTX wiring project.

Our Product Introduction





Ttap Waterproof Solutions





Compatiable With Optitap(Corning),H connector(Amphenol)

FTTX Enclosure Box Application



Waterproof Rate IP68.(1M ,1hour) Applicable optical cable 2.0x3.0mm,3.0mm ,5.0mm

≤0.50dB Insertion loss Return loss ≥55dB

Conform to YD T 2341.1-2011 End face performance Mechanical durability 1000 times

2.0x3.0mm (Ttap Fast ≥30N; 2Minute

Connector)

2.0mm,3.0mm (Ttap Connector) Cable tension ≥30N; 2Minute

5.0mm (Ttap Connector) ≥70N; 2Minute

Torsion of optical cable ≥15N

Allow 10 drops under 1.5m height without abnormal performance Drop performance

2.0x3.0mm (Ttap Fast -10 ~+70

Operation

2.0mm,3.0mm (Ttap Connector) -40 ~+80

> 5.0mm (Ttap Connector) Long term operation under 90% relative humidity ,70

Hot and humid working environment











Outdoor Fiber Optic Cable Assembly



Main Products









Fiber Optic Cable

MPO/MTP









Product inquiry



Our Company

















PACKING & DELIVERY







Wholesale orders

FAQ

- How many staff's we have?
 Answer: About 250 well-trained staff and engineers

- What certificate we have? nawer. ISO 9001: 2015, RoSH, CE, High and New Tech Enterprise Certificate



Uson Beijing Silk Road Enterprise Management Services Co.,LTD





