Our Product Introduction

₫

more products please visit us on polyknitfabric.com

#### Pre-embedded FTTH Fiber Optic Drop Cable SC/UPC Fast Field Assembly Connector

#### Basic Information

• Place of Origin: Guangdong, China

• Brand Name: DYS ISO9001 Certification: SC/UPC Model Number: Minimum Order Quantity: 10 pieces

\$0.28 - \$0.55/pieces

 Packaging Details: Individual Package or plastic box 20000 Piece/Pieces per Day Supply Ability:



#### **Product Specification**

Fast Connector • Type: FTTH

Warranty Time:

Product Name: Fiber Optic SC Field Assembly Connector

Color: Green.Blue Connector Type: SC/UPC

 Fiber Cable Type: 2.0mm 3.0mm Cable, 3x2mm Flat Cable

Insert Loss: Less 0.3db Return Loss: More Than 55db Fiber Type: SM/MM,G652D,G657A1

 Operate Temperature: -40 to85

FTTH FTTB FTTX Network Application:

• Port: Shenzhen



#### More Images









#### **Product Description**

#### **Product Description**

# CONNECTOR WORKSHOP

#### Pre-embedded FTTH Fiber Optic Drop Cable SC/UPC Fast Field Assembly Connector

Installed in order to ensure the quality and efficiency of research and development of the high ratio of the fiber optic fast in products. Pressure welding parts adopt new unique structure design, installation no injecting, no grinding, no material. With embedded optical fiber type structure

Installed with high quality and high success rate and fast and other characteristics .It Can be reused and easy to carry

#### **APPLICATIONS**


Used to open the FTTH fiber terminal end.
In the box, cabinet, such as wiring into the box.
Off the back of the accidents such as fiber, maintenance.
LAN, wan, data and video transmission.
The construction of the fiber end user access and maintenance.
Optical fiber access of mobile base station.

#### **FEATURES**

Single fiber, SC/LC/ST/FC-based connector In-line connection available Operating temperature: -40° to 85°C Cable Diameter Range: 2.0mm, 3.0mm, 2.0\*3.0mm



# Simple and easy to use, fast installation





Take out the tail sleeve and put it into the optical cable







Strip the outer sheath of the optical cable and keep the covering layer. The length is 50mm.



FTTH drop cable stripper





Use Fiber Optic Stripper Strip the fiber coating





Fiber Optic Stripper+Fixed length





Remove impurities with alcohol





Alcohol bottle + paper towel







Cut fiber optical



Optical Fiber cleaver





The optical fiber penetrates from the tail of the connector, causing the optical fiber to bend







Move the switch up to the top



09

Put on the blue protective sleeve, the assembly is complete

# Product display





#### PRODUCT PARAMETERS

	Туре	SM-UPC		SM-APC		MM-UPC	
		Typical	MAX	Typical	MAX	Typical	MAX
	Insertion loss	≥45dB	≤0.35dB	≤0.15	≤0.35dB	≤0.05	≤0.30dB
	Return loss	≥45dB		≥55dB		≥30dB	

Durability 500 mating cycles
Working temperature -40 to +85

#### Main Products









MPO/MTP















# DYS CERTIFICATE



# **COMPANY PROFILE**



























# PACKING & DELIVERY





Sample

Wholesale orders

### **FAQ**

- How many staff's we have?
   Answer: About 250 well-trained staff and engineers.
- When our company be established?
   Answer: We started from year 2008.

- 4. What is the area of the factory?

Product inquiry





(Tyson) Beijing Silk Road Enterprise Management Services Co.,LTD





19 Xinjian Gongmen Road, Haidian District, Beijing, China