Our Product Introduction

₫

more products please visit us on polyknitfabric.com

SC UPC APC Single Mode G657A Simplex 1core 2core Indoor outdoor FTTH **Drop fiber optic Patch cord**

Basic Information

• Place of Origin: Guangdong, China

• Brand Name: DYS

Certification: ISO9001,ROHS, RoHS, ce

SC Model Number:

Minimum Order Quantity: 100 pieces

\$1.95/pieces >=100 pieces Packaging Details: each one in plastic bag Supply Ability: 50000 Piece/Pieces per Day



Product Specification

Fiber Optic Cable . Type:

Number Of Conductors:

• Product Name: SC Optical Fiber Drop Cable

Use: FTTH

Single Mode/Multimode Core Type:

Patch Cord Wavelength: 1310/1550nm

SC/APC-SC/APC (UPC Optional) Connector Type:

Color: Yellow/orange/Aqua

. No. Of Fiber:

 Surface Level: PC/UPC/APC Outer Sheath: PVC/LSZH

Port: Shenzhen Or Hongkong



More Images









Product Description

Product Description

SC/PC APC Pigtail GJYXFCH Type Fiber Optic Drop Cable Patch Cord

- (1) FTTH drop cable patch cord is specially for FTTH application, it can be used indoor or outdoor to access building.
 (2) FTTH drop cable patch cord is used to connect to the end users' homes, widely applied in access networks and FTTH indoor cabling.
 (3) FTTH drop cables are good to use for fiber to the home last mile solution, we provide FTTH drop cable with different counts from 1, 2, 4, to
- (4) FTTH drop cable patch cord can be made with LC, SC, FC, ST, LC/APC, SC/APC, FC/APC and other types of connectors.
- FEATURES
- 1.Price-Competitive 2.Low Insertion Loss & PDL
- 2.Low insertion Loss & PDL
 3.Factory-terminated and Tested
 4.Fiber Options: G.652 /G.657/OM1/OM2/OM3 and PM Panda Fiber
 5.Connector Options: FC/SC/LC/ST/MU/E2000/MT-RJ/MPO/MTP
 6.Pollshing Options: PC/UPC/APC
 7.Feature Connector with Ceramic Ferrules

- APPLICATION
- 1.Access Network 2.Telecom/CATV Systems

FTTH drop cable fiber optic patch cord Performance Parameter

Name FTTH drop cable fiber optic patch cord




zirconia ceramics ferrule Ferrule type IL ≤0.3dB RL ≥55dB 1,2,4 to 12 ≥1000 times Fiber core Durability 3.1*2.0 or 5.0*2.0mm PVC or LSZH 1310 1550nm Wavelength Jacket Length 1~1000 meter Working temperature -40 ~+80









Cable Structure

FRP or Steel Member 250u Coloring Fiber Outer jacket LSZH

Cable Structure











Our Company











19 Xinjian Gongmen Road, Haidian District, Beijing, China