



40CH 100GHz Flat-top Athermal AWG DWDM MUX DEMUX Module

Our Product Introduction

for more products please visit us on polyknitfabric.com

Basic Information

- Place of Origin: Guangdong, China
- Brand Name: DYS
- Model Number: DWDM
- Minimum Order Quantity: 2 pieces
- Price: \$35.00 - \$500.00/pieces
- Packaging Details: Plastic box
Carton box
Or as customers requirements
- Supply Ability: 10000 Set/Sets per Day



Product Specification

- Type: DWDM Module
- Use: FTTX, FTTX
- Channel Number: DWDM MUX/DEMUX-40ch
- Channel Spacing: 100Ghz
- Number Of Channels: 40
- Operating Wavelength: C-band
- Operating Temperature: -5~75
- Input/Output Connector: FC, SC, LC Optional
- Input/Output Length: 0.5m, 1m Or Customized
- Pigtail Diameter: 0.9mm
- Port: Shenzhen



More Images



Product Description

Product Description

DWDM Mux/Demux Athermal AWG Module 40 Channel AWG

DYS rack-mounted 40-channel DWDM multiplexer (Mux) and Demultiplexer (DeMux) chassis provide excellent solution for infrastructure savings by aggregating 40 different wavelengths onto a single fiber. These 1U products are protocol transparent. All 40 channels are in the C-band with spacing of 100 GHz between channels using high quality AWG Gaussian technology.

APPLICATION

DWDM Metro and Long Haul Networks Fiber savings for Data Centers connectivity


FEATURES

High isolation Low insertion loss Dual power supply Can be management by console and NMS Epoxy-free optical path Low total integrated crosstalk Excellent stability & reliability Excellent wavelength accuracy & stability Athermal design


Our Product Introduction



for more products please visit us on polyknitfabric.com



Drawing:



Parameter	Value
Number of Channels	40
Channel Spacing	100Ghz
Operating Wavelength	C-band
Passband Frequency	±0.1nm
Wavelength Accuracy	±50pm
Insertion Loss	<6.0dB
Consistency of Insertion Loss	<1.2dB
Insertion Loss Flatness	<0.5dB
0.5dB Passband	>0.2nm
1dB Passband	>0.4nm
3dB Passband	>0.6nm
20dB Passband	<1.2nm
Adjacent Channel Isolation	≥25dB

Non-Adjacent Channel Isolation	≥30dB
Total Crosstalk	22 dB
Return Loss	≥40dB
Polarization Dependent Loss	<0.5ps
Polarization Mode Dispersion	<0.5ps
Maximum Load Optical Power	24dBm
Monitoring Range of Optical Power	-35dBm ~ +23dBm
Connector Form	LC/UPC
Operating Temperature	-10~+65
Relative Humidity	95%
Dimensions	19-inch 1U rack (440 x 220 x 44mm)



Main Products



DYS CERTIFICATE

- 1 One-stop Solution Service
- 2 Products made by DYS own factory with competitive price, good quality and fast delivery time

Reliability Testing Laboratory

- Manual Image Measuring Machine
- Automatic Insertion Force Testing Machine
- Tensile Testing Machine
- High/Low Temperature Circulating Machine
- IPX6 Pressure Water Immersion Testing Machine
- Fiber Bending and Torsion Testing Machine
- Salt Spray Testing Machine
- Corrosion Testing Machine
- Three Directions Vibration Test Machine



PACKING & DELIVERY



FAQ

1. Do you provide OEM ODM service ?
Yes, we can print your logo or label on the products or on the box.
2. How can you guarantee the quality ?
Build on our perfect quality management system, all of our products were 100% tested before the shipment.
3. What is your delivery time ?
Generally, sample: 3-5 working days; formal order: 7-10 working days.
4. What's the method of shipment?
We accept all shipment, such as Delivery, ocean transport, land transport, airport transport.
5. What's the Payment?
We accept all payments, such as LC, TT, DP, DA, Paypal, Western Union, Money Gram.

Product inquiry

Send us inquiry, you will get full catalog.



Beijing Silk Road Enterprise Management Services Co.,LTD



13299345678



13299345678@163.com



polyknitfabric.com

19 Xinjian Gongmen Road, Haidian District, Beijing, China